

## Fælge med isvejst nav

Fælgttype	Nav	For dæk dimension	
EG 200 x 50 S	55 x 12 Sølv	200 x 50	
GR 200 x 50 S	60 x 20 Sølv		
EG 1.50 - 3 D	60 x 25 mm	250 x 3	
EK 1.50 - 3 D	6004/6004-25		
GG 1.50 - 3 D	85-13 mm		
GK 1.50 - 3 D	6004-85-13 mm		
ER 2.10 x 4 S	75 x 20 mm		250 x 4
ER 2.10 x 4 S	85 x 20 mm	300 x 4	
ER 2.10 x 4 S	85 x 20 mm Sølv	400 x 4	
GR 2.10 x 4 S	75 x 20 mm Sølv		
GR 2.10 x 4 S	85 x 20 mm Sølv		
EK 2.10 x 4 S	6204/6005-25		
EK 2.10 x 4 S	6204/6005-30		
GG 2.10 x 4 S	95-13 mm		
GR 2.10 x 4 S	95-13 mm		
GK 2.10 x 4 S	6004-95-13 mm		
GK 2.10 x 4 D	6004-95-13 mm		
GK 2.10 x 4 S	6005-95-17 mm		
GK 2.10 - 4 D	6005-95-17 mm		
EG 2.10 x 4 S	85 x 25 mm	300 x 4	
EK 2.10 - 4 D	6204/6005-25	400 x 4	
EK 2.10 - 4 D	6204/6005-30	4.10/3.50 x 4	
EK 2.10 - 4 D	6204/6005-25 GALV	11 x 400 x 4	
GG 2.10 x 4 S	120-13 mm		
GR 2.10 x 4 S	120-13 mm		
GK 2.10 x 4 S	6004-120-13 mm		
GK 2.10 - 4 D	6004-120-13 mm		
GK 2.10 x 4 S	6005-120-17 mm		
GK 2.10 - 4 D	6005-120-17 mm		
GK 2.10 - 4 D	6005-120-17 mm Forstærket		
EG 2.50 x 6 S	85 x 25 mm	3.50 x 6	
EK 2.50 x 6 S	6204/6005-25	400 x 6	
GG 2.50 x 6 S	120-13 mm	4.10/3.50 x 6	
GG 2.50 x 6 S	120-17 mm	13 x 500 x 6	
GK 2.50 x 6 S	6204-120-17 mm		